MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				









MODEL NO			SWTE		
MATERIAL			HOUSING-ABS		
			LENS-PC		
			COVER-ABS		
			FILTER LENS-PC		
COLOR OF LENS			RED( ), AMBER( ), GREEN( )		
FLASHING PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC12V ~ DC24V	0.08W	MAX. 0.130A LAYER2
			AC110V		0.050A LAYER2
			AC220V		0.025A LAYER2
VOLUME			MAX. 90dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP55		
CABLE ENTRY			ϕ12 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STEADY/ FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE					
		f	m	ⓒ	v
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
-	-	-	-	1	-

DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20

TITLE: SWTE OUTLINE DRAWING

MODEL: SWTE

DWG. NO.: SWTE_OUT

SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1

Qlight

A4(297X210)