



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			EQ100		
MATERIAL			HOUSING-ABS		
			LENS-PC		
			-		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.			120 ~ 140		
FLASHES PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC24V	MAX. 0.085A	
			AC220V	MAX. 0.140A	
VOLUME			MAX. 90dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP44		
CABLE ENTRY			ø6 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED SIMULATED REVOLVING/STROBE		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5			J.Y.KIM	J.Y.KIM		J.W.KIM	DATE
	6~30	±0.1	±0.2	±0.5	±1							3
	30~120	±0.15	±0.3	±0.8	±1.5							2022.03.16
	120~400	±0.2	±0.5	±1.2	±2.5			TITLE EQ100 OUTLINE DRAWING			MODEL EQ100	
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				EQ100 OUTLINE DRAWING			EQ100_OUT	
	10~50	±0°30'	±1°	±2°				Qlight			DWG. NO.	
	50~120	±0°20'	±0°30'	±1°							SCALE	SHEET
	120~400	±0°10'	±0°13'	±0°30'							N/S	1/1